




# PTZ-6322SR-X33DUP-C

## 2MP 33x Starlight IR Network PoE+ PTZ Dome Camera

- 33X Optical Zoom, Accurate and fast focusing
- Starlight image sensor w. f/1.5 zoom lens for clearer night image
- Smart IR, up to 150 m IR distance
- Optical glass window with higher light transmittance
- IR anti-reflection window to increase the infrared transmittance
- H.265, H.264, MJPEG triple stream + Smart Encoding
- ONVIF Conformance
- Built in EIS (Electronic Image Stabilization)
- More effective heat dissipation system
- Intelligent temperature control technology
- 6 KV surge protection designed for network interface



### Specifications

Sensor	1/2.8", 2 megapixel, progressive scan, CMOS
Shutter	Auto/Manual, 1/6~1/100000 s
Iris	F1.5
Lens	4.5 ~ 148.5 mm (33x optical zoom), 76.8° (wide) ~ 2.1° (tele)
Zoom/Focus	Motor drive
Min. Illumination	Colour: 0.001 lux (F1.5, AGC ON), 0 lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
IR Range	Up to 150m IR range
S/N	>55dB
WDR	120dB WDR
Max. Resolution	1920 × 1080 @30fps
Video Compression	H.265 + Smart Encode, H.264, MJPEG
Frame Rate	1080P (1920*1080): Max. 30 fps; 720P (1280*720): Max. 30 fps; D1 (720*576): Max. 25 fps
HLC / EIS	Supported / Supported
Video Streaming	Triple
OSD / Privacy Mask	Up to 8 OSDs / Up to 8 areas
Behavior Detection	Intrusion, crossing line, motion detection (22x18 grid / 4 area)
Exception Detection	Audio detection
Intelligent Identification	Face detection
Statistical Analysis	People counting
General functions	Watermark, IP Address Filtering, Tampering Alarm, Access Policy, ARP Protection, RTSP Authentication, User Authentication
Audio Compression	G.711a/G.711u
Two-way audio	Supported
Storage	Micro SD, up to 128 GB with ANR (Automatic Network Recovery) Function
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, (Telnet default: OFF)
Compatible Integration	ONVIF(Profile S, Profile G), API
Audio I/O	Audio cable, Input: impedance 35 kΩ; 2 V [p-p], Output: impedance 600 Ω; 2 V [p-p]
Alarm I/O	1/ 1
Network	1 RJ45 10M/100M Base-TX Ethernet
Pan Range / Pan Speed	360° (endless) / 0.1°/s ~ 240°/s, Preset speed: 300°/s
Tilt Range / Tilt Speed	-15° ~ +90° (auto reverse) / 0.1° ~ 80°/s, Preset speed: 240°/s
Prestes / Patrols / Patterns	Max. 1024 presets / Max 16 patrols, up to 32 preset positions per patrol / Max 16 patterns with 15 minutes per pattern. <b>Note:</b> Total number of Patterns + Patrols = 16
Power	12 V DC ±25% or PoE+ (IEEE802.3 at, PSE required), Power consumption: 16 ~ 30W
Dimensions (Ø x H), Weight	Ø215 x 344 mm, 3kg
Working Environment	-40°C ~ +65°C, Humidity ≤ 95% RH(non-condensing)
Ingress Protection	IP66