

3MP Dual Light Network PT hybrid light camera

PT-23-40WAL



Key Features



- 2304*1296@20fps in the main stream
- Ultra 265, H.265, H.264
- Support cross line detection and intrusion detection
- Support digital WDR (Wide Dynamic Range)
- Built-in Mic & Speaker, support two-way audio, offer better interaction
- Intelligent perimeter protection, include cross line, intrusion based on human body detection
- Based on target classification, smart intrusion prevention significantly reduce false alarm caused by leaves, birds and lights etc., accurately focus on human
- Smart IR, up to 30m IR and 30m warm light distance, suitable for more scenes
- Self-contained bracket, support two kinds of mounting
- Supports 256 GB Micro SD card
- Wi-Fi connection and easy installation
- IP66 ingress protection
- The front face is made of grapheme, which has better heat dissipation and more environmental protection

Specifications

PT-23-40WAL					
Camera					
Sensor	1/2.8" progressive scan, 3.0 megapixel, CMOS				
Min. Illumination	Colour:0.005 lux (F1.6, AGC ON) 0 lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Shutter	Auto/Manual, shutter time: 1s ~ 1/100000s				
WDR	Digital				
S/N	>52 dB				
Lens					
Lens type	4mm				
Digital Zoom	4x				
Iris	Fixed; F1.6				
Field of View (H)	90.5°				
Field of View (V)	44.4°				
Field of View (D)	111.3°				
DORI					
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4mm	73.5	29.4	14.7	7.3
Illuminator					
IR Range	Up to 30m				
Warm Light Range	Up to 30m				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Video					
Video Compression	Ultra 265, H.265, H.264				
Frame Rate	Main Stream: 3MP (2304*1296), Max 20fps; Sub Stream: 640*360, Max 20fps;				
Video Bit Rate	128 Kbps ~ 6 Mbps				
ROI	Up to 8 areas				
OSD	Up to 2 OSDs				
Privacy Mask	Up to 4 areas				
Image					
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2				
Digital Noise Reduction	2D/3D DNR				
Smart IR	Support				
Flip	Normal/Flip Vertical/Flip Horizontal/180°				
HLC	Support				
BLC	Support				
Defog	Digital Defog				
Intelligent					
Behavior Detection	Cross Line detection, Intrusion detection based on human body detection				
Human Body Detection	Support				
Events					
Basic Detection	Motion detection, Audio detection				

Auto tracking	Support
General Function	Access Policy, RTSP Authentication, User Authentication
Audio	
Audio Compression	G.711U, G.711A
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz
Storage	
Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR
Network	
Protocols	IPv4, TCP, UDP, DHCP, RTSP, DNS, DDNS, NTP, HTTP, HTTPS, 802.1x, SSL
Compatible Integration	ONVIF (Profile S, Profile G), API
Client	GuardStation Guard-Live
Web Browser	Plug-in required live view: IE 10 and above
Wifi	
Wireless Standards	IEEE802.11b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Wireless Range	Up to 130 m (The performance varies based on actual environment)
Channel Bandwidth	20 MHz Support
Modulation Mode	802.11b: CCK, QPSK, BPSK 802.11g/n: OFDM/HT
Security	64/128-bit WEP, WPA-PSK/WPA2-PSK
Transmit Power	802.11b: 17±1.5dBm @11Mbps 802.11g: 14±1.5dBm @ 54Mbps 802.11n: 12.5±1.5dBm @150Mbps
Receive Sensitivity	802.11b: -90dBm @11Mbps (Typical) 802.11g: -75dBm @54Mbps (Typical) 802.11n: -74dBm @150Mbps (Typical)
Transmission Rate	802.11b: 11Mbps 802.11g: 54Mbps 802.11n: up to 150Mbps
Wireless Standards	IEEE802.11b/g/n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Pan & Tilt	
Pan Range	0° ~ 345°
Pan Speed	1°/s ~ 40°/s
	Preset speed: 40°/s
Tilt Range	0° ~ 90°
Tilt Speed	1°/s ~ 30°/s
	Preset speed: 30°/s
Number of Presets	256
Home Position	Support
Interface	
Built-in Mic	Support
Built-in Speaker	Support

Wi-Fi	Support
Network	1x RJ45 10M/100M Base-TX Ethernet
General	
Power	DC 12V ± 25%
	Power consumption: Max 10W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions (Ø x H)	Φ118mm*118mm*199mm
Weight	0.53kg
Working Environment	-30°C ~ 60°C, Humidity: ≤95% RH (non-condensing)
Surge Protection	4kV
Reset Button	Support
Protection	Ingression protection: IP66

Dimensions

